

UV-B measuring head type 1B.3

UV-B- sensitivity

Long UV radiation (above 323 nm) makes people tan and has positive effects on the human immune system. Shorter UV-radiation in contrast may cause irreversible damage and is listed in a recommendation by CIE (Commission Internationale de l'Eclairage) which summarizes all action spectra that may cause damage to the human skin.


This recommendation is standardized in German DIN 5050.

A popular example is the UVI sunburn index.

UV-B measuring head type 1B.3

The measuring head independently determines UV-B-radiation from 280nm - 320nm.

Measuring results are allowing immediate conclusions about medically and biologically relevant connections within this band of radiation. The measuring head is used in medicine, biological research, weather information and forecast systems, in climate research and for public information in general. The measuring head type 1B.3 has a weatherproof aluminum housing. The dome is made of plastic (PMMA). The values are cosine corrected.




Technical specifications:

measuring range UV-B spectr. sensitivity UV-B max. spectr. sensitivity sensor system working temperature signal output

power

time to switch on time to switch off installation connector diffusor housing-dome cosine correction linearity absolute error weight

0 - ca. 5 W/m² 280nm - 320nm 315nm SiC interf. filter -30°C - +60°C | -22 - +140°F 0V - 5V/0V-10V*/ 4mA-20mA/0mA-20mA** +10V - +24V / 750µA < 1 s < 1 s 2 screws M4 in the bottom bottom. downward PTFE PMMA error f2 < 3% < +/-3% < +/-10% 400g | 14 oz



Specifications are subject to change without notice.

Indium Sensor Virchowstr. 7 15366 Neuenhagen Germany Tel: +49(0)3342 80239 Fax: +49(0)3342 207886

