

## Infrared measuring head type 8.5

## Infrared radiation

The direct and diffuse solar radiation in the range from 700 nm up to 5000 reaching the ground is called infrared radiation.

## Infrared measuring head type 8.5

The sensor detects almost 30 % of the sunlight in the range of 800 nm to 1100 nm including the most relevant part of IR.

Measuring results are allowing immediate conclusions about medically and biologically relevant connections by comparing them to other spectral ranges.


The measuring head may be used in medicine, biological research, weather information and forecast systems, in climate research and for public information in general.

The measuring head may be used in medicine, biological research, weather information and forecast systems, in climate research and for public information in general.

The aluminum housing is weatherproof, the dome is made of plastic or flat glass.

The measuring results are cosine corrected.





## **Technical specifications**


measuring range global spectral sensitivity max. spectral sensitivity working temperature signal output power supply installation

connector
diffusor
dome
cosine correction
linearity
abs. error
residual voltage (E=0)
weight

800 nm - 1100 nm 950 nm -20 °C - +60 °C 0 V - 2 V or the like +5 V - +18 V 2 screws M4 in the bottom of the case sideward PTFE PMMA/flat glass error f2 < 6 % < 1 % < 10 mV ca. 170 g | 6 oz

0 - approx. 400 W/m<sup>2</sup>

Specifications are subject to change without prior notice.



Indium Sensor Virchowstr. 7 D - 15366 Neuenhagen

Tel: +49(0)3342 80239 Fax: +49(0)3342 207886